



Impact Wrenches

The PRO wrenches consist of a wide range of tools to suit your needs. PRO Compact are light weighted tools with composite housing and twin hammer mechanism for the best

power-to-weight ratio. All impact wrenches are built for speed and comfort. Regardless of your choice within the PRO range the tool will do the job for you.



PRO COMPACT LINE IMPACT WRENCHES

High-powered. Ultralight. A smooth operator.

Perfect for tackling the toughest industrial jobs, PRO Compact Impact Wrenches deliver the best power-to-weight ratio within the PRO range.

Powered by an advanced twin hammer mechanism, these compact impacts deliver virtuoso performance and state-of-the-art vibration damping and noise reduction technology.

PRO COMPACT W2309

Square drive	7/16 Hex QC
Clutch type	Twin hammer
Capacity	M14
Torque range	220 - 360 Nm
Max torque fwd	400 Nm
Free speed	10 000 r/min
Weight	1,3 kg
Length	175 mm
Air consumption	8.3 l/s
Air inlet thread	1/4" BSP
Recommended hose size	10 mm (3/8")
Sound level	85 dB(A)
Vibration level	5 m/s ²
Ordering No.	8434 1245 09



PRO COMPACT W2310

Square drive	3/8" (10 mm)
Clutch type	Twin Hammer
Capacity	M14
Torque range	220-360 Nm
Max torque fwd	400 Nm
Free speed	10 000 r/min
Weight	1.25 kg
Length	160 mm
Air consumption	8.3 l/s
Air inlet thread	1/4" BSP
Recommended hose size	10 mm (3/8")
Sound level	85 dB(A)
Vibration level	5 m/s ²
Ordering No.	8434 1245 10



PRO COMPACT W2311

Square drive	1/2" (12.7 mm)
Clutch type	Twin Hammer
Capacity	M14
Torque range	220-360 Nm
Max torque fwd	400 Nm
Free speed	10 000 r/min
Weight	1.25 kg
Length	160 mm
Air consumption	8.3 l/s
Air inlet thread	1/4" BSP
Recommended hose size	10 mm (3/8")
Sound level	85 dB(A)
Vibration level	5 m/s ²
Ordering No.	8434 1245 11





PRO COMPACT LINE IMPACT WRENCHES



PRO COMPACT W2315

Square drive	1/2" (12.7 mm)
Clutch type	Twin Hammer
Capacity	M22
Torque range	320-610 Nm
Max torque fwd	780 Nm
Free speed	7 000 r/min
Weight	2.0 kg
Length	190 mm
Air consumption	12 l/s
Air inlet thread	1/4" BSP
Recommended hose size	10 mm (3/8")
Sound level	85 dB(A)
Vibration level	6.75 m/s ²
Ordering No.	8434 1245 15



PRO COMPACT W2320

Square drive	3/4" (19 mm)
Clutch type	Twin Hammer
Capacity	M27
Torque range	340-870 Nm
Max torque fwd	1050 Nm
Free speed	4 000 r/min
Weight	3.8 kg
Length	240 mm
Air consumption	19 l/s
Air inlet thread	3/8" BSP
Recommended hose size	13 mm (1/2")
Sound level	85 dB(A)
Vibration level	4.2 m/s ²
Ordering No.	8434 1245 20

PRO EXPLOSION PROOF IMPACT WRENCHES

ATEX-certified for hazardous environments

PRO Compact XP tools meet stringent European standards and comply with ATEX Directive I M2 II 2G IIB T4 II2D 135°. These explosion-proof products are designed for use in hazardous environments, such as coal mines, petrochemical plants or wherever a spark-reduced safety tool is required.



PRO COMPACT W2315XP

Square drive	1/2" (12.7 mm)
Clutch type	Twin Hammer
Capacity	M22
Torque range	320-610 Nm
Max torque fwd	780 Nm
Speed	7 000 r/min
Weight	2.52 kg
Length	190 mm
Vibration level	6.75 m/s ²
Sound level	93 dB(A)
Air consumption	12 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8434 1245 17



PRO COMPACT W2320XP

Square drive	3/4" (19 mm)
Clutch type	Twin Hammer
Capacity	M24
Torque range	340-870 Nm
Max torque fwd	1 050 Nm
Speed	4 000 r/min
Weight	4.72 kg
Length	240 mm
Vibration level	4.2 m/s ²
Sound level	85 dB(A)
Air consumption	19 l/s
Suitable air hose	13 mm (1/2")
Air inlet thread	3/8" BSP
Ordering No.	8434 1245 22



IMPACT WRENCHES

PRO W2110 HEX

Quick change	HEX
Clutch type	Double hammer
Capacity	M12
Torque range	13-70 Nm
Max torque fwd	94 Nm
Speed	8 000 r/min
Weight	0.98 kg
Length	160 mm
Vibration level	<2.5 m/s ²
Sound level	84 dB(A)
Air consumption	8.7 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8434 1244 20



PRO W2111 3/8"

Square drive	3/8" (10 mm)
Clutch type	Double hammer
Capacity	M12
Torque range	13-70 Nm
Max torque fwd	94 Nm
Speed	8 000 r/min
Weight	0.98 kg
Length	154 mm
Vibration level	<2.5 m/s ²
Sound level	84 dB(A)
Air consumption	8.7 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8434 1244 23



PRO W2210A 3/8"

Square drive	3/8" (10 mm)
Clutch type	Single hammer
Capacity	M14
Torque range	70-180 Nm
Max torque fwd	270 Nm
Speed	9 000 r/min
Weight	1.7 kg
Length	160 mm
Vibration level	<2.5 m/s ²
Sound level	85 dB(A)
Air consumption	8.7 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8434 1244 31



PRO W2211 1/2"

Square drive	1/2" (12.7 mm)
Clutch type	Single hammer
Capacity	M14
Torque range	70-180 Nm
Max torque fwd	270 Nm
Speed	9 000 r/min
Weight	1.7 kg
Length	160 mm
Vibration level	< 2.5 m/s ²
Sound level	85 dB(A)
Air consumption	8.7 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8434 1244 33



PRO W2214XT 1/2"

Square drive	1/2" (12.7 mm)
Clutch type	Single hammer
Capacity	M20
Torque range	150-570 Nm
Max torque fwd	640 Nm
Speed	7 300 r/min
Weight	2.4 kg
Length	200 mm
Vibration level	3.4 m/s ²
Sound level	88 dB(A)
Air consumption	11.6 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8434 1244 70



PRO W2215XTC 1/2" Composite

Square drive	1/2" (12.7 mm)
Clutch type	Twin hammer
Capacity	M22
Torque range	350-650 Nm
Max torque fwd	820 Nm
Speed	7 500 r/min
Weight	2.1 kg
Length	190 mm
Vibration level	5.7 m/s ²
Sound level	94 dB(A)
Air consumption	11.4 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8434 1244 80



IMPACT WRENCHES

PRO W2219 3/4"

Square drive	3/4" (19 mm)
Clutch type	Single hammer
Capacity	M22
Torque range	450-700 Nm
Max torque fwd	1 030 Nm
Speed	3 800 r/min
Weight	5.1 kg
Length	255 mm
Vibration level	3.3 m/s ²
Sound level	91 dB(A)
Air consumption	12.2 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8434 1244 37



PRO W2220 3/4"

Square drive	3/4" (19 mm)
Clutch type	Twin Hammer
Capacity	M30
Torque range	650-1500 Nm
Max torque fwd	1 762 Nm
Speed	3 800 r/min
Weight	6.3 kg
Length	270 mm
Vibration level	9.0 m/s ²
Sound level	84 dB(A)
Air consumption	18 l/s
Suitable air hose	13 mm (1/2")
Air inlet thread	3/8" BSP
Ordering No.	8434 1244 39



PRO W2225C 1"

Square drive	1" (25.4 mm)
Clutch type	Single hammer
Capacity	M30
Torque range	400-1040 Nm
Max torque fwd	1 660 Nm
Speed	3 800 r/min
Weight	10.1 kg
Length	290 mm
Vibration level	3.6 m/s ²
Sound level	92 dB(A)
Air consumption	19.9 l/s
Suitable air hose	13 mm (1/2")
Air inlet thread	3/8" BSP
Ordering No.	8434 1244 54



PRO W2226C 1"

Square drive	1" (25.4 mm)
Clutch type	Twin Hammer
Capacity	M30
Torque range	650-1500 Nm
Max torque fwd	1 762 Nm
Speed	3 800 r/min
Weight	6.8 kg
Length	270 mm
Vibration level	9.0 m/s ²
Sound level	97 dB(A)
Air consumption	18 l/s
Suitable air hose	13 mm (1/2")
Air inlet thread	3/8" BSP
Ordering No.	8434 1244 56



PRO W2227 1"

Square drive	1" (25.4 mm)
Clutch type	Twin hammer
Capacity	M30
Torque range	670-1200 Nm
Max torque fwd	1300 Nm fwd
Speed	5 000 r/min
Weight	6,8 kg
Length	355 mm
Vibration level	8,5 m/s ²
Sound level	104 dB(A)
Air consumption	18 l/s
Suitable air hose	13 mm (1/2")
Air inlet thread	3/8" BSP
Ordering No.	8434 1244 58



PRO W2227-LA

Square drive	1" (25,4 mm)
Clutch type	Twin hammer
Capacity	M30
Torque range	670 - 1200 Nm
Max torque fwd	1300Nm
Speed	5000 r/min
Weight	7.1 kg
Length	507 mm
Vibration level	8,5 m/s ²
Sound level	104 dB(A)
Air consumption	18 l/s
Suitable air hose	13 mm (1/2")
Air inlet thread	3/8" BSP
Ordering No.	8434 1244 59





IMPACT WRENCHES INCLUDING POWER SOCKETS



W2310 KIT

3/8" impact wrench with a 5pcs socket delivered in a practical carrying box.

Metric sockets 8, 10, 13, 15, 17

Ordering No. 8434 1245 12



W2311 KIT

1/2" impact wrench with a 5pcs socket delivered in a practical carrying box.

Metric sockets 10, 13, 14, 15, 17

Ordering No. 8434 1245 13

W2315 KIT

1/2" impact wrench with a 5pcs socket delivered in a practical carrying box.

Metric sockets 13, 15, 17, 19, 21

Ordering No. 8434 1245 16

W2214XT KIT

1/2" impact wrench with a 5pcs socket delivered in a practical carrying box.

Metric sockets 13, 15, 17, 19, 21

Ordering No. 8434 1244 71

W2215XTC KIT

1/2" impact wrench with a 5pcs socket delivered in a practical carrying box.

Metric sockets 13, 15, 17, 19, 21

Ordering No. 8434 1244 81

Protective covers

Model	Ordering No.
W2214XT	4112 0817 00
W2215XTC	4112 1347 00
W2219	4112 0396 00
W2315	4112 0396 15



Max forward torque is measured with a trigger time of 5 sec. Max torque in reverse is between 10-20% higher than the forward torque to ensure that a joint can be loosened with the same tool.