



Drills

Strong and robust, PRO drills deliver superior hole quality for demanding applications. Highly accurate and efficient, these tools offer unmatched speed, power, accuracy

and smooth silent-running operation. Features include air exhaust through the handle and an ergonomic handle for working comfort.



Choose the right drill for the right material

Material/cutting speed							
Model	r/min	Mild steel 20-30 m/ min	Alloy steel 5-15 m/min	Cast iron 15-20 m/min	Aluminium and bronze 50-80 m/min	Wood and board 80-150 m/min	Composite 50-100 m / min
D2112	5 400	1.0- 2.0	-	-	2.5- 5.0	4.0- 8.0a	1.0- 5.0
D2116	2 400	2.5- 6.0	1.0- 3.0	2.0- 4.0	8.0-13.0a	8.0-13.0a	-
D2163	2 000	2.5- 6.0	1.0- 3.0	2.0- 4.0	8.0-13.0a	8.0-13.0a	-
D2121	750	8.0-13.0	3.0- 8.0	7.0-13.0	-	-	-
D2148-R	750	8.0-13.0	3.0- 8.0	7.0-13.0	-	-	-

a) Drill size larger than standard chuck capacity.

DRILLS

PRO D2112

Chuck capacity	0-6.5 mm
Mount	3/8"-24 UNF
Output	350 watt
Speed	5 400 r/min
Weight	1.0 kg
Length incl chuck	206 mm
Vibration level	< 2.5 m/s ²
Sound level	78 dB(A)
Air consumption	10.0 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8421 0405 05



PRO D2116

Chuck capacity	1.5-10 mm
Mount	3/8"-24 UNF
Output	350 watt
Speed	2 400 r/min
Weight	1.0 kg
Length incl chuck	211 mm
Vibration level	< 2.5 m/s ²
Sound level	78 dB(A)
Air consumption	10.0 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8421 0405 13



PRO D2121

Chuck capacity	2-13 mm
Mount	3/8"-24 UNF
Output	340 watt
Speed	750 r/min
Weight	1.4 kg
Length incl chuck	248 mm
Vibration level	< 2.5 m/s ²
Sound level	78 dB(A)
Air consumption	10.0 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8421 0405 21



PRO D2148-R Reversible

Chuck capacity	2-13 mm
Mount	3/8"-24 UNF
Output	250 watt
Speed	750 r/min
Weight	1.45 kg
Length incl chuck	248 mm
Vibration level	< 2.5 m/s ²
Sound level	77 dB(A)
Air consumption	10.0 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8421 0407 03



PRO D2163

Chuck capacity	1.5-10 mm
Mount	3/8"-24 UNF
Output	330 watt
Speed	2 000 r/min
Weight	1.1 kg
Length incl chuck	242 mm
Height incl chuck	128 mm
Vibration level	< 2.5 m/s ²
Sound level	77 dB(A)
Air consumption	9.3 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8421 0410 08



Drills with quick change chuck on page 26



DRILLS QUICK CHANGE CHUCKS

PRO D2112Q



Chuck capacity	1-10 mm
Mount	3/8"-24UNF
Output	350 watt
Speed	5 400 r/min
Weight	1.0 kg
Length incl chuck	211 mm
Vibration level	< 2.5 m/s ²
Sound level	78 dB(A)
Air consumption	10 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8421 0405 10

PRO D2116Q



Chuck capacity	1-10 mm
Mount	3/8"-24 UNF
Output	350 watt
Speed	2 400 r/min
Weight	1.0 kg
Length incl chuck	211 mm
Vibration level	< 2.5 m/s ²
Sound level	78 dB(A)
Air consumption	10.0 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8421 0405 15

PRO D2121Q



Chuck capacity	1.5-13 mm
Mount	3/8"-24 UNF
Output	340 watt
Speed	750 r/min
Weight	1.4 kg
Length incl chuck	248 mm
Vibration level	< 2.5 m/s ²
Sound level	78 dB(A)
Air consumption	10.0 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8421 0405 25

Optional accessories for D2163

	Ordering No.
Exhaust air hose	4150 1077 80
Support handle	4110 1355 85

PRO D2148-RQ



Chuck capacity	1.5-13 mm
Mount	3/8"-24UNF
Output	250 watt
Speed	750 r/min
Weight	1.45 kg
Length incl chuck	248 mm
Vibration level	< 2.5 m/s ²
Sound level	77 dB(A)
Air consumption	10 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	3/8" BSP
Ordering No.	8421 0407 05

Optional accessories for all drills

Key chucks key included, mount 3/8"-24 UNF	Ordering No.
0-6.5 Chuck capacity mm (Standard with D2112)	4021 0444 00
1.5-10 Chuck capacity mm (Standard with D2116, D2163)	4021 0446 00
2-13 Chuck capacity mm (Standard with D2121, D2148-R)	4021 0447 00
1-10 mm Keyless chuck (Standard with D2112Q, D2116Q)	4021 0497 90
1.5-13 mm Keyless chuck (Standard with D2121Q, D2148-RQ)	4021 0496 90
Quick-change chuck for 1/4" bits mount 3/8"-24 UNF	4021 0443 00
Drill depth stop to be used with support handle	4110 1370 80 4110 1355 81
Use in/for 2112/16/21 Exhaust air hose	4210 2053 00
2148-R Exhaust air hose (D2112, D2116, D2121)	4210 2929 00