



Air Screwdrivers

We offer a full range of air screwdrivers for general repair and body shops with a variety of handle styles, speeds and torque adjustments to handle the toughest jobs.

CP780 Air Screwdriver



- Cushion clutch with external clutch adjustment
- Built-in quick change chuck
- Convenient forward/reverse valve
- Ideal for general repair and body shop work
- Free Speed: 1,800 rpm

CP781 Air Screwdriver



- Cushion clutch with external clutch adjustment
- Built-in quick change chuck
- Convenient forward/reverse valve
- Ideal for general repair and body shop work
- Free Speed: 800 rpm

CP782 Air Screwdriver



- Cushion clutch with external clutch adjustment
- Built-in quick change chuck
- Convenient forward/reverse valve
- Ideal for general repair and body shop work
- Free Speed: 1,800 rpm

CP783 Air Screwdriver



- Cushion clutch with internal clutch adjustment
- Compact design for easy handling
- Magnetic bit holder
- Ideal for general repair and body shop work
- Free Speed: 2,000 rpm

	CP780	CP781	CP782	CP783
Chuck Size [in.]	1/4, Fem Hex QC	1/4, Fem Hex QC	1/4, Fem Hex QC	1/4, Fem Hex QC
Free Speed [rpm]	1,800	800	1,800	2,000
Minimum Torque [Nm (in.lbs)]	2.83 (25)	2.83 (25)	3.5 (31)	1.13 (10)
Maximum Torque [Nm (in.lbs)]	4.97 (44)	8.47 (75)	4.97 (44)	2.83 (25)
Weight [kg (in.)]	1.13 (2.5)	1.36 (3)	1.13 (2.5)	0.6 (1.33)
Length [mm (in.)]	210 (8.25)	226 (8.88)	245 (9.63)	226 (8.88)
Actual Air Consumption [l/min (CFM)]	453 (16)	453 (16)	453 (16)	453 (16)
Air Inlet Thread Size NPTF [in.]	1/4	1/4	1/4	1/4
Minimum Hose Size [mm (in.)]	10 (3/8)	10 (3/8)	10 (3/8)	10 (3/8)
Sound dB(A) Pressure	98.3	99.5	93.9	88.1
Vibration m/s ²	2.7	3	17	4.4

Listed specifications are for reference only. Please check documents in each tool.

See page 02 for specific test methods