



Air Impact Wrenches

We know a good impact can be the most important tool in the shop, so we've worked hard to offer you the most. The most innovation resulting in the patented CP Turbo motor system and patented clutch mechanisms like our latest, the *Spring Hammer*, providing smooth operation and extreme durability. The most versatility by offering a wide selection for every type of application. All with power, speed and comfort. Finally, your toughest jobs have met their match.

CP719 1/4" Heavy Duty Air Impact Wrench



- Fast, with 47Nm of torque at 7,000 rpm's
- Compact and lightweight for easy access to the tight spots. Only 115mm long at 1.13kg
- One hand push button forward/reverse power regulator
- Perfect for small engine repair, small fasteners and body shops
- **Ultimate Torque: 47Nm**

CP719QC 1/4" Heavy Duty Hex Air Impact Wrench



- Same great features as the CP719 plus a 1/4" hex chuck
- **Ultimate Torque: 47Nm**

CP721 3/8" Heavy Duty Air Impact Wrench



- Rocking dog clutch for smooth operation and extreme durability
- Energy efficient motor for maximum performance
- Great tool for small engine repair, bench work and transmissions
- **Ultimate Torque: 102Nm**

CP722 3/8" Heavy Duty Air Impact Wrench



- Rocking dog clutch for smooth operation and extreme durability
- Easy manoeuvring with 360° air inlet swivel
- Butterfly throttle for comfort and control
- Packed with plenty of power for bench work, carburetors, ignitions, body panels, transmissions, oil pans, and small engine repair
- **Ultimate Torque: 102Nm**

CP724H 3/8" Heavy Duty Air Impact Wrench



- DYNA-PACT oil bath clutch delivers smooth operation and extended durability
- One hand push button forward/reverse power regulator. 4 positive power settings. Full power in reverse
- Handle exhaust directs air away from the work area while 360° air inlet swivel prevents hose kinks
- Power and economy for general repair, transmission work, exhaust systems and body shops
- **Ultimate Torque: 271Nm**

CP727 3/8" Heavy Duty Air Impact Wrench



- Durable clutch mechanism for smooth operation and longer life
- Comfortable ergonomic handle design
- Handle exhaust with 360° air inlet swivel to prevent hose kinks
- Ideal for transmission work, exhaust system, body shops and general repair in the 3/8" range
- **Ultimate Torque: 244Nm**

	CP719	CP719QC	CP721	CP722	CP724H	CP727
Square Drive [in.]	1/4	1/4 hex	3/8	3/8	3/8	3/8
Working Torque Range [Nm (ft.lbs)]	7-27 (5-20)	7-27 (5-20)	7-68 (5-50)	7-68 (5-50)	54-230 (40-170)	54-230 (40-150)
Max. Torque@90PSI Rev. [Nm (ft.lbs)]	47 (30)	47 (30)	102 (75)	102 (75)	271 (200)	244 (180)
Free Speed [rpm]	7,000	7,000	11,000	9,500	8,500	6,800
Weight [kg (lb)]	1.13 (2.5)	1.13 (2.5)	1.19 (2.63)	0.9 (2)	1.41 (3.1)	1.59 (3.5)
Length [mm (in.)]	114 (4.5)	114 (4.5)	146 (5.75)	146 (5.75)	152 (6)	152 (6)
Avg. Air Consumption [l/min, (CFM)]	57 (2)	57 (2)	71 (2.5)	71 (2.25)	85 (3)	85 (3)
Air Inlet Thread Size NPTF [in.]	1/4	1/4	1/4	1/4	1/4	1/4
Sound dB(A) Pressure	87.6	87.6	84.1	86.3	93	95
Vibration m/s ²	<2.5	<2.5	4.9	<2.5	<2.5	4.3

Listed specifications are for reference only. Please check documents in each tool.

See page 02 for specific test methods

AIR IMPACT WRENCHES

CP726H 1/2" Heavy Duty Air Impact Wrench



- DYNA-PACT oil bath clutch delivers smooth operation and extended durability
- One hand push button forward/reverse power regulator, 4 positive power settings. Full power in reverse
- Handle exhaust with 360° air inlet swivel to prevent hose kinks
- Great tool for transmission work, exhaust systems, bench work, body shops and general repair
- **Ultimate Torque: 271Nm**

CP734H 1/2" Super Duty Air Impact Wrench



- DYNA-PACT oil bath clutch delivers smooth operation and extended durability
- One hand push button forward/reverse power regulator, 4 positive power settings. Ultimate power in reverse
- Handle exhaust with 360° air inlet swivel to prevent hose kinks
- Power and economy for general repair, transmission work, exhaust systems and body shops
- **Ultimate Torque: 576Nm**

CP734HK-Metric

- **1/2" Air Impact Wrench Kit**
- Packed in a heavy duty carrying case, this kit includes the CP734H impact wrench plus a set of 5 sockets: 14, 16, 17, 19 & 22mm
- **Ultimate Torque: 576Nm**

CP734HK

- **1/2" Air Impact Wrench Kit**
- Same great features as the CP734HK with 1/2", 5/8", 3/4", 7/8" & 15/16" sockets



CP7740 1/2" Lightweight Heavy Duty Air Impact Wrench



- 1/2" impact wrench made with magnesium components
- Highest power to weight ratio in the 1/2" impact market
- A compact size of just 160mm long
- Air inlet swivel
- Great tool for tough nuts in tight spots
- Only 1.25Kg
- **Ultimate Torque: 675Nm**

CP7740-2

1/2" Lightweight Air Impact Wrench

- Same great features as the CP7740 with a 2" extended shank
- **Ultimate Torque: 675Nm**



CP7740Q

1/2" Lightweight Air Impact Wrench

- Same great features as the CP7740 with lower noise
- Unique external muffler system that can be easily cleaned or replaced
- **Ultimate Torque: 675Nm**



CP7740Q-2

1/2" Lightweight Air Impact Wrench

- Same great features as the CP7740Q with a 2" extended shank
- **Ultimate Torque: 675Nm**



NEW

INTRODUCING
MgDRIVEN™
Technology

ONLY **1.25Kg**

	CP726H	CP734H	CP7740	CP7740-2	CP7740Q	CP7740Q-2
Square Drive [in.]	1/2	1/2	1/2	1/2	1/2	1/2
Working Torque Range [Nm (ft.lbs)]	54-230 (40-170)	34-420 (25-310)	60-450 (45-350)	60-450 (45-350)	60-450 (45-350)	60-450 (45-350)
Max. Torque@90PSI Rev. [Nm (ft.lbs)]	271 (200)	576 (425)	675 (500)	675 (500)	675 (500)	675 (500)
Free Speed [rpm]	8,500	8,400	5,400	5,400	5,400	5,400
Weight [kg (lb)]	1.41 (3.1)	2.33 (5.13)	1.25 (2.7)	1.33 (2.9)	1.31 (2.9)	1.39 (3.0)
Length [mm (in.)]	152 (6)	232 (9.13)	160 (6.3)	210 (8.3)	160 (6.3)	210 (8.3)
Avg. Air Consumption [l/min. (CFM)]	85 (3)	106 (3.75)	149 (5.25)	149 (5.25)	149 (5.25)	149 (5.25)
Air Inlet Thread Size NPTF [in.]	1/4	1/4	1/4	1/4	1/4	1/4
Sound dB(A) Pressure	94	93	87.9	87.9	82.8	82.8
Vibration m/s ²	<2.5	3.4	5.9	5.9	5.9	5.9

See page 02 for specific test methods

Listed specifications are for reference only. Please check documents in each tool.

CP7733 1/2" Heavy Duty Air Impact Wrench



- Patented **Springhammer** clutch provides smooth operation and extreme durability
- Comfort and control with new ergonomic grip and trigger
- Low air consumption and high torque makes this tool the most efficient in its class
- Packed with power and speed, this economical 1/2" impact wrench is the right tool for general automotive service, body shop, farm and light truck work.
- **Ultimate Torque: 746Nm**

CP7733-2 1/2" Heavy Duty Air Impact Wrench

Same great features as the CP7733 with a 2" extended anvil for tyre work

- **Ultimate Torque: 746Nm**

CP749-2 1/2" Super Duty Air Impact Wrench



Same great features of the CP749 with a 2" extended anvil for tyre work

- **Ultimate Torque: 827Nm**

CP749-2K 1/2" Super Duty Air Impact Wrench Kit
Packed in a heavy duty carrying case, this kit includes the CP749-2 impact wrench plus two flip sockets: (3/4", 13/16") and (19mm, 21mm) and a bottle of CP Air Tool oil

- **Ultimate Torque: 827Nm**

CP749 1/2" Super Duty Air Impact Wrench



- Tackle the tough jobs with the power and speed of this true workhorse
- Patented **Springhammer** clutch provides smooth operation and extreme durability
- One hand push button forward/reverse power regulator, 4 positive power settings in forward and ultimate power in reverse
- Compact design with comfortable contoured handle
- **Ultimate Torque: 827Nm**

CP749K-Metric 1/2" Super Duty Air Impact Wrench Kit

Packed in a heavy duty carrying case, this kit includes the CP749 impact wrench plus 5 sockets: 14, 16, 17, 19 & 22mm and a bottle of CP Air Tool oil

- **Ultimate Torque: 827Nm**

CP749K 1/2" Super Duty Air Impact Wrench Kit

Same great features as the CP749K with 1/2", 5/8", 3/4", 7/8", 15/16" sockets

CP7750 1/2" Extreme Duty Air Impact Wrench



- Still the Most Powerful 1/2" Impact Wrench on the planet, with 1085Nm of ultimate torque
- With innovative, patented new motor technology, the Turbo 2.0 pounds the most torque faster
- Best in industry at 1,500 bpm. That makes removing stubborn fasteners quick and easy
- Four position power regulator with 2 speeds in forward and 2 in reverse
- Professional touch trigger and ergonomic cushion grip handle provide comfort and control, even at high torque levels
- **Ultimate Torque: 1085Nm**

CP7750-2 1/2" Extreme Duty Air Impact Wrench



Same great features as the CP7750 with a 2" extended anvil for tyre work

- **Ultimate Torque: 1085Nm**

ULTIMATE TORQUE 1085Nm

	CP7733	CP7733-2	CP749	CP749-2	CP7750	CP7750-2
Square Drive [in.]	1/2	1/2	1/2	1/2	1/2	1/2
Working Torque Range [Nm (ft.lbs)]	34-542 (25-400)	34-542 (25-400)	68-610 (50-450)	68-610 (50-450)	68-746 (50-550)	68-746 (50-550)
Max. Torque@90PSI Rev. [Nm (ft.lbs)]	746 (550)	746 (550)	827 (625)	827 (625)	1085 (800)	1085 (800)
Free Speed [rpm]	6,900	6,900	6,400	6,400	6,400	6,400
Weight [kg (lb)]	2.5 (5.6)	2.7 (5.9)	2.49 (5.5)	2.49 (5.75)	2.31 (5.1)	2.27 (5)
Length [mm (in.)]	180 (7.1)	231 (9.1)	178 (7)	229 (9)	244 (9.6)	193 (7.6)
Avg. Air Consumption [l/min. (CFM)]	106 (4.75)	106 (4.75)	156 (5.5)	5.75	170 (6)	170 (6)
Air Inlet Thread Size NPTF [in.]	1/4	1/4	1/4	1/4	1/4	1/4
Sound dB(A) Pressure	96	96	96	96	94	94
Vibration m/s ²	4	4	4.9	4.9	4.4	4.4

Listed specifications are for reference only. Please check documents in each tool.

See page 02 for specific test methods

AIR IMPACT WRENCHES

CP772H 3/4" Heavy Duty Air Impact Wrench



- Smoothest operating 3/4" impact on the market with unmatched durability
- One hand push button forward/reverse power regulator. 4 positive power settings in forward and ultimate power in reverse
- Handle exhaust with 360° air inlet swivel to prevent hose kinks
- New comfortable contoured handle grip
- Ideal for spring work, truck and bus maintenance, farm machinery and construction equipment
- **Ultimate Torque: 1356Nm**

CP772HK-Metric

3/4" Heavy Duty Air Impact Wrench Kit
Packed in a heavy duty carrying case, this kit includes the CP772H plus 4 Metric deep sockets: 24, 27, 30 & 32 mm

CP772HK

3/4" Heavy Duty Air Impact Wrench Kit
Same great features as the CP772HK with 15/16", 1", 1-1/16" and 1-1/8" deep sockets

CP772H-6

3/4" Heavy Duty Air Impact Wrench
Same great features as the CP772H with a 6" extended anvil for tyre work



CP776 3/4" Super Duty Air Impact Wrench



- Compact size with high output
- Rugged clutch mechanism for extended durability under heavy use
- One hand push button forward/reverse power regulator. 4 positive power settings in forward and ultimate power in reverse
- Perfect for spring work, pinion nut and tractor pad removal, truck tyre work and major engine tear downs
- **Ultimate Torque: 1559Nm**

CP776-6

3/4" Super Duty Air Impact Wrench
Same great features as the CP776 with a 6" extended anvil for tyre work



CP7763 3/4" Super Duty Air Impact Wrench



- Compact size with high output
- Twin Hammer clutch for power and greater durability
- Three position power regulator with forward/reverse directional control
- Quiet handle exhaust
- **Ultimate Torque: 1627Nm**

CP7763-6

3/4" Super Duty Air Impact Wrench
Same great features as the CP7763 with a 6" extended shank



	CP772H	CP772H-6	CP776	CP776-6	CP7763	CP7763-6
Square Drive [in.]	3/4	3/4	3/4	3/4	3/4	3/4
Working Torque Range [Nm (ft.lbs)]	203-949 (150-700)	203-949 (150-700)	271-1017 (200-750)	271-1017 (200-750)	136-1288 (100-950)	136-1288 (100-950)
Max. Torque@90PSI Rev. [Nm (ft.lbs)]	1356 (1,000)	1356 (1,000)	1559 (1,150)	1559 (1,150)	1627 (1,200)	1627 (1,200)
Free Speed [rpm]	4,200	4,200	4,500	4,500	6,300	6,300
Weight [kg (lb)]	4.76 (10.5)	5.28 (11.63)	5.67 (12.5)	6.21 (13.7)	5.25 (11.57)	6.28 (13.85)
Length [mm (in.)]	245 (9.6)	394 (15.5)	222 (8.75)	375 (14.75)	224 (8.8)	381 (15)
Avg. Air Consumption [l/min. (CFM)]	170 (6)	170 (6)	220 (7.75)	220 (7.75)	212 (7.5)	212 (7.5)
Air Inlet Thread Size NPTF [in.]	3/8	3/8	3/8	3/8	3/8	3/8
Sound dB(A) Pressure	96	96	99.1	99.1	96	96
Vibration m/s ²	4.9	4.9	6.8	6.8	9	9

See page 02 for specific test methods

Listed specifications are for reference only. Please check documents in each tool.

CP7773 1" Heavy Duty Air Impact Wrench



- Compact size with high output
- Twin Hammer clutch for power and greater durability
- Three position power regulator with forward/reverse directional control
- Quiet handle exhaust
- **Ultimate Torque: 1627Nm**



NEW

- CP7773-6
1" Heavy Duty Air Impact Wrench**
Same great features as the CP7773 with a 6" extended shank

CP897-6 1" Heavy Duty Air Impact Wrench



- Same great features as the CP897 with a 6" extended anvil for tyre work

**CP897SP-6
1" Heavy Duty Air Impact Wrench**

- Same great features as the CP897 with a 6" extended anvil and #5 spline

CP898 1" Heavy Duty Air Impact Wrench



- Lightweight at only 10.2kg
- Rocking dog clutch for smooth operation and extreme durability
- Convenient reverse valve for easy directional changes
- High performance motor maximizes out put while minimizing air consumption
- Perfect for high volume truck tyre shops
- **Ultimate Torque: 1763Nm.**

CP897 1" Heavy Duty Air Impact Wrench



- Our lightest 1" air wrench at only 7.37kg
- Convenient reverse valve
- High performance motor maximizes output while minimizing air consumption
- Teasing throttle for easy bolt starting
- Perfect for high volume truck tyre shops
- **Ultimate Torque: 1763Nm**



**CP898-6
1" Heavy Duty Air Impact Wrench**

- Same great features as the CP898 with a 6" extended anvil for tyre work
- **Ultimate Torque: 1763Nm**

	CP7773	CP7773-6	CP897	CP897-6	CP897SP-6	CP898	CP898-6
Square Drive [in.]	1	1	1	1	#5 spline	1	1
Working Torque Range [Nm (ft.lbs)]	136-1288 (100-950)	136-1288 (100-950)	203-1085 (150-800)	203-1085 (150-800)	203-1085 (150-800)	203-1085 (150-800)	203-1085 (150-800)
Max. Torque@90PSI Rev. [Nm (ft.lbs)]	1627(1,200)	1627 (1,200)	1763 (1,300)	1763 (1,300)	1763 (1,300)	1763 (1,300)	1763 (1,300)
Free Speed [rpm]	6,300	6,300	3,800	3,800	3,800	4,200	4,200
Weight [kg (lb)]	5.47 (12.05)	6.33 (13.95)	7.37 (16.25)	8.62 (19)	8.62 (19)	10.2 (22.5)	10.88 (24)
Length [mm (in.)]	224 (8.8)	381 (15)	349 (13.75)	502 (19.75)	502 (19.75)	343 (13.5)	495 (19.5)
Avg. Air Consumption [l/min. (CFM)]	212 (7.5)	212 (7.5)	184 (6.5)	184 (6.5)	184 (6.5)	227 (8)	227 (8)
Air Inlet Thread Size NPTF [in.]	3/8	3/8	1/2	1/2	1/2	1/2	1/2
Sound dB(A) Pressure	96	96	101	101	101	103	103
Vibration m/s ²	9	9	7.5	7.5	7.5	11	11

Listed specifications are for reference only. Please check documents in each tool.

See page 02 for specific test methods

AIR IMPACT WRENCHES

CP797 1" Heavy Duty Air Impact Wrench



- Long known as the workhorse of the truck tyre industry
- Rocking dog clutch for smooth operation and extreme durability
- Teasing throttle for easy bolt starting
- Convenient reverse valve for easy directional changes
- Choice of professional mechanics for high volume tyre work on trucks, buses and heavy equipment
- **Ultimate Torque: 1898Nm**

CP797-6 1" Super Duty Air Impact Wrench

- Truck tyre tool of choice
- Same great features as the CP797 with a 6" extended anvil for tyre work
- Choice of professional mechanics for high volume tyre work on trucks, buses and heavy equipment
- **Ultimate Torque: 1898Nm**

CP797SP-6 1" Super Duty Air Impact Wrench

- Same great features as the CP797 with a 6" extended anvil and #5 spline
- **Ultimate Torque: 1898Nm**

CP797TL-6 1" Torque Limiting Air Impact Wrench



- Same great features as the CP797 with a 6" extended anvil and torque limited
- Great for reducing the risk of over torquing lug nuts on truck wheels

CP797TLSP-6 1" Super Duty Air Impact Wrench

- Same great features as the CP797 with a 6" extended anvil, #5 spline, and torque limited

CP893 1" Heavy Duty Air Impact Wrench



- High performance motor maximizes power output
- One hand push button forward/reverse power regulator. 4 positive power settings in forward and ultimate power in reverse
- Adjustable dead handle for operator comfort
- Ideal for spring work, tractor pad removal, and off road equipment repair
- **Ultimate Torque: 1898Nm**

CP893-6 1" Heavy Duty Air Impact Wrench

- Same great features as the CP893 with a 6" extended anvil for tyre work

CP7778 1" Heavy Duty Air Impact Wrench



- Three position power regulator with directional control
- Angled down exhaust directs air away from operator
- High-efficiency 6 vane motor
- **Ultimate Torque: 1966Nm**

CP7778-6 1" Impact Wrench

- Same great features as the CP7778 with a 6" extended anvil

CP7778SP-6 #5 Spline Drive Impact Wrench

- Same great features as the CP7778-6 with a #5 spline drive anvil



	CP797	CP797-6 / CP797SP-6	CP797TL-6 / CP797TLSP-6	CP893	CP893-6	CP7778	CP7778-6 / CP7778SP-6
Square Drive [in.]	1	1 / #5 spline	1 / #5 spline	1	1	1	1 / #5 spline
Working Torque Range [Nm (ft.lbs)]	203-1220 (150-900)	203-1220 (150-900)	813** (600)	271-963 (200-710)	271-963 (200-710)	136-1491 (100-1100)	136-1491 (100-1100)
Max. Torque@90PSI Rev. [Nm (ft.lbs)]	1898 (1,400)	1898 (1,400)	1898 (1,400)	1898 (1,400)	1898 (1,400)	1966 (1,450)	1966 (1,450)
Free Speed [rpm]	4,200	4,200	2,150	4,400	4,400	5,000	5,000
Weight [kg (lb)]	12.25 (27)	13.49 (29.75)	13.61 (30)	10.43 (23)	10.75 (23.7)	10.1 (22.2)	11.5 (25.4)
Length [mm (in.)]	394 (15.5)	565 (22.25)	629 (24.75)	292 (11.5)	445 (17.5)	355 (13.4)	513 (20.2)
Avg. Air Consumption [l/min. (CFM)]	283 (10)	283 (10)	163 (5.75)	290 (10.25)	290 (10.25)	248 (8.75)	248 (8.75)
Air Inlet Thread Size NPTF [in.]	1/2	1/2	1/2	3/8	3/8	1/2	1/2
Sound dB(A) Pressure	110	110	110	97.8	97.8	101	101
Vibration m/s ²	7.6	7.6	7.6	9.4	9.4	9.1	9.1

**813Nm on Budd Wheel steel rims, other applications, torque may vary

See page 02 for specific test methods

Listed specifications are for reference only. Please check documents in each tool.

CP7775 1" Heavy Duty Air Impact Wrench



- The MOST power in its class
- At only 10.9kg, reduces operator fatigue
- Directs air away from operator and work area
- Four position power control in forward and reverse
- Ergonomically designed handles and trigger
- **Ultimate Torque: 2102Nm**

CP7775-6 1" Heavy Duty Air Impact Wrench

- Same great features as the CP7775 with a 6" extended anvil for tyre work
- **Ultimate Torque: 2102Nm**

CP7775SP-6 1" Heavy Duty Air Impact Wrench

- CP7775 with a 6" extended anvil and #5 spline
- **Ultimate Torque: 2102Nm**

CP7774-6 1" Super Duty Air Impact Wrench



Same great features as the CP7774 with a 6" extended anvil.

- **Ultimate Torque: 2,102Nm**

CP796 1" Super Duty Air Impact Wrench



- Offers the most torque at 2712Nm
- Best power to weight ratio in a 1" air wrench
- Compact housing design for ease of use in tight areas
- Industrial quality and durability in an automotive tool
- Ideal for spring work, tractor pad removal and off road equipment repair
- **Ultimate Torque: 2712Nm**

CP796SP

1" Super Duty Air Impact Wrench

Same great features as the CP796 with a #5 spline

CP894 1" Heavy Duty Air Impact Wrench



- Oil bath clutch for smooth operation and extended durability
- One hand push button forward/reverse power regulator, 3 positive power settings in forward and ultimate power in reverse
- Adjustable side handle for added support
- Ideal for spring work, tractor pad removal, and off road equipment repair
- **Ultimate Torque: 2305Nm**

CP5000 1" Super Duty Air Impact Wrench

CP7774 1" Super Duty Air Impact Wrench



- Handle exhaust directs air away from work area
- Three position power regulator in forward and reverse to match the power to the job
- Extreme durability for everyday work
- **Ultimate Torque: 2,373Nm**



- Our strongest and most powerful 1" impact with extended anvil
- Four position power regulator
- Controllable throttle provides easy bolt starting
- 7" extended anvil for easy access to heavy equipment tyres
- Easy to use forward/reverse valve for quick directional changes
- Ideal for high volume tyre work on trucks, buses and heavy equipment
- **Ultimate Torque: 2712Nm**

	CP7775	CP7775-6	CP894	CP7774	CP7774-6	CP796 / CP796SP	CP5000
Square Drive [in.]	1	1	1	1	1	1 / #5 spline	1
Working Torque Range [Nm (ft.lbs)]	136-1627 (100-1,200)	136-1627 (100-1,200)	407-1627 (300-1,200)	136-1763 (100-1,300)	136-1491 (100-1,100)	407-1898 (300-1,400)	502-2169 (370-1,600)
Max. Torque@90PSI Rev. [Nm (ft.lbs)]	2102 (1,550)	2102 (1,550)	2305 (1,700)	2373 (1,750)	2102 (1,550)	2712 (2,000)	2712 (2,000)
Free Speed [rpm]	5,500	5,500	4,100	5,000	5,000	4,100	4,100
Weight [kg (lb)]	10.6 (22.2)	12.5 (25.4)	11.34 (25)	10.07 (22.2)	11.6 (25.5)	9.07 (20)	13.83 (30.5)
Length [mm (in.)]	340 (13.4)	513 (20.2)	298 (11.75)	267 (10.5)	432 (17)	241 (9.5)	572 (22.5)
Avg. Air Consumption [l/min. (CFM)]	248 (8.75)	248 (8.75)	319 (11.25)	234 (8.25)	234 (8.25)	368 (13)	336 (11.8)
Air Inlet Thread Size NPTF [in.]	1/2	1/2	1/2	1/2	1/2	1/2	1/2
Sound dB(A) Pressure	96	96	99.6	100.9	100.9	101	103.1
Vibration m/s ²	9.1	9.1	5	8.7	8.7	13	8.9

Listed specifications are for reference only. Please check documents in each tool.

See page 02 for specific test methods